



Trijicon[®]

Combat Optics

Trijicon SRS[™]
(Sealed Reflex Sight)



Optic Features:

- ▼ No "Tube-Effect"
- ▼ ACOG Ruggedness
- ▼ 10 Brightness Settings, including 3 NVG Settings
- ▼ Dual Power Sources: Solar Cell & AA Battery
- ▼ Parallax Free
- ▼ Waterproof To 165 Feet (50 Meters)
- ▼ Auto-Locking, Self Adjusting Lever Mount
- ▼ 1.75 MOA Dot
- ▼ No "Auto-Off" Feature

The SRS is a feature packed sealed reflex sight that benefits from a truly innovative design. Its unique optical design virtually eliminates the "tube-effect" common with other red dot sights which essentially provides no obstruction to the shooters FOV. This translates to lightning fast target engagements at CQB distances with no distraction from the shooter's situational awareness. The SRS is powered by a solar panel and a single AA battery. The unique solar enhancement provides years of life from a single battery. Lastly, the SRS comes with a self-adjusting, auto-locking lever mount that is easily manipulated with only one hand and no tools.




Specifications

Optical Magnification	1X
Clear Aperture	1.1" (28mm)
Field of View	23m at 100m with 4" eye relief
Elevation Adjustment Range	$\pm 1^{\circ}15'$ = ± 75 MOA = ± 22.2 mils
Windage Adjustment Range	$\pm 1^{\circ}15'$ = ± 75 MOA = ± 22.2 mils
Adjustment Increments	Easily adjustable without special tools. 1/2 MOA per click (1/2 inch per click @ 100 yds)
Reticle	1.75 MOA (0.5 milliradians) red dot
Reticle Illumination	LED
Battery Type	1 AA (E91), Alkaline or Lithium (preferred) battery
Battery Life	Over 3 years of continuous use at brightness setting 7 of 10 at 70°F (21°C) with supplied Lithium battery. Over 2.5 years of continuous use at brightness setting 7 of 10 at 70°F (21°C) with standard Alkaline battery.
Photovoltaic Cell	Automatically provides supplemental power when outside during daylight conditions, further increasing battery life.
Brightness Settings	10 brightness settings, including 3 Night-Vision and 1 Super-Bright
Dimensions	3.75" L x 2.5" W x 2.4" H (97 x 64 x 61 mm) without mount
Weight	10.9 oz. (310g) with supplied lithium battery
Weight (with mount)	13.8 oz. (390g) with supplied lithium battery and mount
Material – Housing	Forged 7075-T6 aluminum, hard coat anodized per MIL-A-8625, Type III, Class 2, dull & non-reflective
Immersion	Waterproof to 165 ft. (50m)
Optical Center	1.57 in. from top of rail

Additional Views



Available Reticles



1.75 MOA

For more information, please call our Military & Law Enforcement Division at 1-540-286-1827 or visit us online at www.trijicon.com.